



Xtended Definition Series



Technical specifications

P3ESR XD

Frequency response	75Hz-20kHz \pm 3dB free space, grille on, smooth off-axis response.
Impedance	6 Ω - easy load
Sensitivity	83dB/2.7v/1m axial
Dimensions	306 x 190 x 184mm (hwd)
Weight	6.1kg

C7ES-3 XD

Frequency response	45Hz-20kHz \pm 3dB free space, grille on, smooth off-axis response
Impedance	6 Ω - easy load
Sensitivity	86dB/2.7v/1m axial
Dimensions	520 x 272 x 305mm (hwd)
Weight	13.2kg

M30.2 XD

Frequency response	50Hz-20kHz \pm 3dB free space, grille on, smooth off-axis response
Impedance	6 Ω - easy load
Sensitivity	85 dB/2.7v/1m axial
Dimensions	460 x 277 x 275mm (hwd)
Weight	11.6kg

SHL5plus XD

Frequency response	40Hz-20kHz \pm 3dB free space, grille on, smooth off-axis response
Impedance	6 Ω - easy load
Sensitivity	86 dB/2.7v/1m
Dimensions	635 x 322 x 300mm (hwd)
Weight	15.8kg

M40.3 XD

Frequency response	35Hz-20kHz \pm 3dB free space, grille on, smooth off-axis response
Impedance	6-8 Ω - easy load
Sensitivity	86 dB/2.7v/1m axial
Dimensions	750 x 432 x 388mm (hwd)
Weight	38kg